

ADVISORY ON THE USE OF THIS DOCUMENT

The information contained in this document has been developed solely for the purpose of providing general guidance to employees of the Goddard Space Flight Center (GSFC). This document may be distributed outside GSFC only as a courtesy to other government agencies and contractors. Any distribution of this document, or application or use of the information contained herein, is expressly conditioned upon, and is subject to, the following understandings and limitations:

- (a) The information was developed for general guidance only and is subject to change at any time;
- (b) The information was developed under unique GSFC laboratory conditions which may differ substantially from outside conditions;
- (c) GSFC does not warrant the accuracy of the information when applied or used under other than unique GSFC laboratory conditions;
- (d) The information should not be construed as a representation of product performance by either GSFC or the manufacturer;
- (e) Neither the United States government nor any person acting on behalf of the United States government assumes any liability resulting from the application or use of the information.

PPM-91-587

Date

September 20, 1991

Division

GSEC

Telephone

731-8954

Location

Lanham

S. Archer-Davies

N. Virmani

T. Perry

A. Sharma

Department

Code 716

Name

K. Sahu *KS*

Department

7809

Subject

Radiation Report on GPEP/PPL

Part Nos. 2299000-1,-2

A radiation evaluation was performed on 2299000-1 and 2299000-2 to determine the total dose tolerance of these parts. A brief summary of the test results is provided below. For detailed information, refer to Tables I through IV and Figure 1.

The total dose testing was performed using a cobalt-60 gamma ray source. During the radiation testing, four parts (two of each part type) were irradiated under bias (see Figure 1 for bias configuration), and two parts (one of each type) were used as control samples. The total dose radiation steps were 25, 50, 100, 300, 600 and 1000 krads. After 1000 krads, parts were annealed at 25°C for 120 and 168 hours (cumulative). The dose rate was between 1.3 - 9.1 krads/hour, depending on the total dose level (see Table II for radiation schedule). After each radiation exposure and annealing treatment, parts were electrically tested according to the test conditions and the specification limits listed in Table III.

Three of the four irradiated parts passed all tests on irradiation to 1Mrads and subsequent annealing at 25°C. One part, SN 212 - 2299000-2, marginally failed VOL3 after the final cumulative exposure of 1Mrads (the VOL3 reading was 408mV against the maximum specification limit of 400mV). However, this part passed after both annealing treatments. All parts passed functionally at all radiation and annealing steps. Table IV provides the mean and standard deviation values for each parameter after different radiation exposures and annealing treatments.

Any further details about this evaluation can be obtained upon request. If you have any questions, please call me at (301) 731-8954.

TABLE I. Part Information

Generic Part Number:	2299000
GPEP/PPL Part Numbers:	2299000-1,-2
GPEP/PPL Control Numbers:	4706 (2299000-1) 4707 (2299000-2)
Charge Number:	C14500
Manufacturer:	Teledyne MicroElectronics
Lot Date Codes:	9106, 9109, 9111, 9047, 9049
Quantity Tested:	6
Serial Numbers of Radiation Samples:	201 (LDC 9109, PN 2299000-1) 202 (LDC 9111, PN " -1) 211 (LDC 9109, PN " -2) 212 (LDC 9106, PN " -2)
Serial Numbers of Control Samples:	200 (LDC 9049, PN 2299000-1) 210 (LDC 9047, PN 2299000-2)
Part Function:	128k x 8 <u>64k x 16 SRAMS</u>
Part Technology:	CMOS
Package Style:	92-Pin DIP
Test Engineer:	J. Lander

← verify if this is correct
How are they configured?
128k x 8-bit?

TABLE II. Radiation Schedule for 2299000-1,-2

EVENTS	DATE
1) Initial Electrical Measurements	08/20/91
2) 25 krads irradiation @ 1250 rads/hr	08/20/91
Post 25 krads Electrical Measurements	08/21/91
3) 50 krads irradiation @ 1250 rads/hr	08/21/91
Post 50 krads Electrical Measurements	08/22/91
4) 100 krads irradiation @ 2630 rads/hr	08/22/91
Post 100 krads Electrical Measurements	08/23/91
5) 300 krads irradiation @ 3300 rads/hr	08/23/91
Post 300 krads Electrical Measurements	08/26/91
6) 600 krads irradiation @ 6800 rads/hr	08/26/91
Post 600 krads Electrical Measurements	08/28/91
7) 1 MRad irradiation @ 9100 rads/hr	08/28/91
Post 1 MRad Electrical Measurements	08/30/91
8) 120 hour annealing	08/30/91
Post 120 hr Electrical Measurements	09/04/91
9) 168 hour annealing	08/30/91
Post 168 hr Electrical Measurements	09/06/91

Notes:

- All parts were radiated under bias at the cobalt-60 gamma ray facility at GSFC.
- All electrical measurements were performed off-site at 25°C.
- Annealing performed at 25°C under bias.

Table III. Electrical Characteristics of 2299000-1,-2

FUNCTIONAL TESTS						
PARAMETER	VCC	VIL	VIH	CONDITIONS	PINS	LIMITS 25C, -55C & 125C
FUNCT # 1	5.0V	0.0V	5.0V	FREQ = 6.25MHz	ALL I/O	VOL<1.5V , VOH>1.5V
FUNCT # 2	5.0V	0.0V	5.0V	FREQ = 6.25MHz	ALL I/O	VOL<1.5V , VOH>1.5V
FUNCT # 3	5.0V	0.0V	5.0V	FREQ = 2.00MHz	ALL I/O	VOL<1.5V , VOH>1.5V
FUNCT # 4	5.0V	0.0V	5.0V	FREQ = 2.00MHz	ALL I/O	VOL<1.5V , VOH>1.5V
DC PARAMETRIC TESTS						
PARAMETER	VCC	VIL	VIH	CONDITIONS	PINS	LIMITS 25C, 55C & 125C
VIH_5.5V	5.5V	0.0V	0.8V	FREQ= 2MHZ	INS	>+0.8V , <+2.0V
VIL_4.5V	4.5V	2.0V	4.5V	FREQ= 2MHZ	INS	>+0.8V , <+2.0V
VOH1	4.5V	0.3V	2.0V	LOAD= -0.3MA	OUTS	>+2.4V , <+5.5V
VOH2	4.5V	0.0V	4.5V	LOAD= -4.0MA	OUTS	>+2.4V , <+5.5V
VOH3	4.5V	0.0V	4.5V	LOAD= 8.0MA	OUTS	>+2.4V , <+5.5V
VOL1	4.5V	0.8V	2.0V	LOAD= +0.3MA	OUTS	> 0.0V , <+0.2V
VOL2	4.5V	0.0V	4.5V	LOAD= +4.0MA	OUTS	> 0.0V , <+0.4V
VOL3	4.5V	0.0V	4.5V	LOAD= +8.0MA	OUTS	> 0.0V , <+0.4V
I IH	5.5V	0.0V	5.5V	VIN = 5.5V	INS	>-100A , <+100A
I IL	5.5V	0.0V	5.5V	VIN = 0.0V	INS	>-100A , <+100A
IOZH	5.5V	0.0V	5.5V	VOUT= 5.5V	OUTS	>-300A , <+300A
IOZL	5.5V	0.0V	5.5V	VOUT= 0.0V	OUTS	>-300A , <+300A
ICCSE	5.5V	0.0V	5.3V	DISABLED DUT	VCC	> 0.0MA , <+8MA
ICCD	5.5V	0.0V	5.3V	FRQ = 1 MHZ	VCC	> 0.0MA , <+80MA
ICCX	5.5V	0.0V	5.3V	F=2MHZ, 1K BLK	VCC	> 0.0MA , <+8MA
AC PARAMETRIC TESTS						
PARAMETER	VCC	VIL	VIH	CONDITIONS	OUTPINS	LIMITS 25C, -55C & 125C
TAA1_LH	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U1 , U9	> 0ns , < 110ns
TAA1_HL	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U1 , U9	> 0ns , < 110ns
TAA2_LH	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U2 , U10	> 0ns , < 110ns
TAA2_HL	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U2 , U10	> 0ns , < 110ns
TAA3_LH	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U3 , U11	> 0ns , < 110ns
TAA3_HL	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U3 , U11	> 0ns , < 110ns
TAA4_LH	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U4 , U12	> 0ns , < 110ns
TAA4_HL	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U4 , U12	> 0ns , < 110ns
TAA5_LH	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U5 , U13	> 0ns , < 110ns
TAA5_HL	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U5 , U13	> 0ns , < 110ns
TAA6_LH	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U6 , U14	> 0ns , < 110ns
TAA6_HL	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U6 , U14	> 0ns , < 110ns
TAA7_LH	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U7 , U15	> 0ns , < 110ns
TAA7_HL	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U7 , U15	> 0ns , < 110ns
TAA8_LH	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U8 , U16	> 0ns , < 110ns
TAA8_HL	4.5V	0.0V	3.0V	F=1.0MHz, VCMP=1.5V	U8 , U16	> 0ns , < 110ns

Comments and Exceptions for Table III

- (1) FUNCTIONAL TESTS ARE PERFORMED AT VCC=5.0V ONLY.
- (2) FUNCTIONAL TESTS #1 & #3 CONSISTS OF THE FOLLOWING PATTERNS :
 - 1 - ALL_ONES
 - 2 - ALL_ZEROS
 - 3 - CHECKERBOARD
 - 4 - INVERSED CHECKERBOARD
- (3) FUNCTIONAL TESTS #2 & #4 CONSISTS OF THE FOLLOWING APG PATTERNS :
 - 1 - "10N" MARCH
 - 2 - ROW_ADDRESS
 - 3 - COL_ADDRESS
 - 4 - SLIDING_DIAGONALLY
 - 5 - PING_PONG
 - 6 - SURROUND
 - 7 - ROW_GALPAT
 - 8 - COL_GALPAT
- (4) VIL & VIH WERE TESTED DYNAMICALLY @ 2MHZ FUNCTIONAL AND GO/NOGO DURING VOHI & VOLI DC TESTS.
- (5) ICCX : STAND BY QUIESCENT CURRENT MEASUREMENT FOR EVERY 1024 ADDRESS LOCATIONS. CONSIST OF THE FOLLOWING PROCEDURE :
 - (a) - WRITE ZEROES (ALL ADDRESSES).
 - (b) - WRITE ONES TO THE FIRST 1024 ADDRESSES.
 - (c) - PERFORM AN ICCSB MEASUREMENTS.
 - (d) - WRITE ZEROES TO THE FIRST 1024 ADDRESSES.
 - (e) - REPEAT STEPS (b)-(d) FOR THE NEXT 1024 ADDRESSES AND SO ON, FOR A TOTAL OF 64 READINGS (64K ADDRESSES).
- (6) TESTS NOT PERFORMED :
 - WRITE/READ CYCLE TIMING PERFORMED GO/NOGO @ 6.25MHz (FUNCT #1 & #2).
 - ONLY ADDRESS ACCESS TIME PROP. DELAYS WERE PERFORMED (TAA TESTS).
 - ALL OTHER AC TESTS ARE NOT BEING PERFORMED WITHIN THIS PROGRAM.
- (7) THIS PROGRAM TESTS FOR CONTINUITY AND OPPOSITE STATE VOL OR VOH TEST.

TABLE IV: Summary of Electrical Measurements
after Total Dose Exposures and Annealing for 2299000-1,-2

1/1, 2/

Parameters	Spec. Limits min max		Initials mean sd		Total Dose Exposure (krads)												Annealing			
					25		50		100		300		600		1000		168 hrs			
					mean	sd	mean	sd	mean	sd	mean	sd	mean	sd	mean	sd	mean	sd		
Func1 @6.25MHz			Pass		Pass		Pass		Pass		Pass		Pass		Pass		Pass		Pass	
Func2 @6.25MHz			Pass		Pass		Pass		Pass		Pass		Pass		Pass		Pass		Pass	
Func3 @ 2MHz			Pass		Pass		Pass		Pass		Pass		Pass		Pass		Pass		Pass	
Func4 @ 2MHz			Pass		Pass		Pass		Pass		Pass		Pass		Pass		Pass		Pass	
VIH	V	0.8	2.0	1.88	.06	1.87	.06	1.86	.06	1.86	.1	1.74	.06	1.73	.04	1.72	.04	1.75	.03	
VIL	V	0.8	2.0	1.58	.03	1.56	.02	1.55	.03	1.53	.03	1.44	.04	1.43	.01	1.40	.02	1.43	.02	
VOH1	V	2.4	4.5	4.48	0	4.48	0	4.48	0	4.48	0	4.48	0	4.48	0	4.48	0	4.48	0	
VOH2	V	2.4	4.5	4.34	.01	4.34	0	4.34	0	4.34	0	4.34	0	4.33	0	4.32	.03	4.33	0	
VOH3	V	2.4	4.5	4.17	.01	4.18	.01	4.18	.01	4.18	.01	4.17	.01	4.16	.01	4.14	.05	4.16	.01	
VOL1	mV	0	200	5	.7	5	.6	5	.5	5	.6	5	.6	5	.6	5	.2	5	.5	
VOL2	mV	0	400	80	2	77	2	77	2	76	2	75	2	76	2	83	28	77	2	
VOL3	mV	0	400	164	4	158	4	157	4	156	4	154	4	154	5	169	54	157	5	
IIH	uA	-10	10	0	0	0	0	0	0	0	0	0	0	0	0	.03	.1	.01	.03	
IIL	uA	-10	10	0	.02	0	.01	0	.01	0	.01	0	.01	0	.01	0	.01	0	.01	
IOZH	uA	-30	30	0	0	0	0	0	0	0	0	0	0	0	0	.09	.15	.02	.05	
IOZL	uA	-30	30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
ICCSB	mA	0	8	.8	.07	.8	.06	.8	.06	.8	.06	.8	.07	.8	.03	.8	.03	.8	.03	
ICCD	mA	0	80	40	5	40	5	40	5	40	5	39	5	39	5	39	5	39	5	
ICCX	mA	0	8	.8	.04	.8	.04	.8	.04	.7	.04	.8	.04	.8	.05	1.2	.5	1.0	.3	

<Table IV continued on next page>

Table IV. (conti)

Parameters	Spec. Limits	Total Dose Exposure (krads)																Annealing	
		Initials		25		50		100		300		600		1000		168 hrs			
		min	max	mean	sd	mean	sd	mean	sd	mean	sd	mean	sd	mean	sd	mean	sd	mean	sd
TAA1_LH	ns	0	110	64	16	63	16	63	16	62	16	61	15	54	10	56	10	57	10
TAA1_HL	ns	0	110	46	3	45	3	46	3	47	4	53	9	57	13	57	15	59	14
TAA2_LH	ns	0	110	63	16	62	16	62	16	62	16	61	15	54	10	55	11	56	10
TAA2_HL	ns	0	110	46	3	45	4	45	4	46	4	52	9	56	13	57	15	58	14
TAA3_LH	ns	0	110	63	16	62	16	62	16	62	16	61	15	54	10	55	11	56	10
TAA3_HL	ns	0	110	46	3	45	3	45	4	46	4	52	9	57	13	57	15	59	14
TAA4_LH	ns	0	110	62	16	61	16	62	16	61	16	60	15	54	10	55	11	56	10
TAA4_HL	ns	0	110	46	3	45	4	45	4	46	4	51	9	56	13	57	15	59	14
TAA5_LH	ns	0	110	63	16	62	16	62	16	62	16	61	15	54	10	55	11	56	10
TAA5_HL	ns	0	110	46	3	45	3	45	3	45	3	52	9	57	13	55	15	57	15
TAA6_LH	ns	0	110	62	16	61	16	61	16	61	16	60	15	54	10	55	11	56	10
TAA6_HL	ns	0	110	46	3	45	3	45	4	45	3	51	9	56	13	55	15	57	15
TAA7_LH	ns	0	110	63	16	62	16	62	16	61	15	61	15	54	10	56	10	56	10
TAA7_HL	ns	0	110	46	3	45	3	45	3	45	3	52	9	57	13	55	15	57	15
TAA8_LH	ns	0	110	62	15	61	15	61	15	61	15	60	14	53	10	55	10	56	10
TAA8_HL	ns	0	110	45	3	45	3	45	4	45	3	51	9	56	13	55	15	56	15

Notes:

1/ The mean and standard deviation values were calculated over the four parts irradiated in this testing. The control samples remained constant throughout the testing and are not included in this table.

2/ Table IV does not contain post 120 hour electrical measurement data. This data is available and can be obtained upon request.

Figure 1. Radiation Bias Circuit for 2299000-1,-2

CH	PINS	92-PIN 2.5" DIP STYLE PACKAGE	PINS	CH
--	GND	1	92	GND
--	GND	2	91	GND
--		3	90	
--	VCC	4	89	VCC
--	VCC	5	88	VCC
--		6	87	
--		7	86	MOEA_ 63
--		8	85	WEA_ 62
--		9	84	DIRTA 61
00	LE	10	83	OEA_ 60
--		11	82	
01	A(00)	12	81	DQA(0) 59
02	A(01)	13	80	DQA(1) 58
03	A(02)	14	79	DQA(2) 57
04	A(03)	15	78	DQA(3) 56
05	A(04)	16	77	DQA(4) 55
06	A(05)	17	76	DQA(5) 54
07	A(06)	18	75	DQA(6) 53
08	A(07)	19	74	DQA(7) 52
--		20	73	
--	VCC	21	72	GND
--	VCC	22	71	GND
--		23	70	
--		24	69	
--		25	68	
--	GND	26	67	VCC
--	GND	27	66	VCC 50
--		28	65	
20	A(08)	29	64	DQB(0) 43
21	A(09)	30	63	DQB(1) 42
22	A(10)	31	62	DQB(2) 41
23	A(11)	32	61	DQB(3) 40
24	A(12)	33	60	DQB(4) 39
25	A(13)	34	59	DQB(5) 38
26	A(14)	35	58	DQB(6) 37
27	A(15)	36	57	DQB(7) 36
--		37	56	
28	EN1_	38	55	DEB_ 35
29	EN2_	39	54	DIRTB 34
30	EN3_	40	53	WEB_ 33
31	EN4_	41	52	MUEB_ 32
--		42	51	
--	VCC	43	50	VCC
--	VCC	44	49	VCC
--		45	48	
--	GND	46	47	GND

Notes for Radiation Bias Circuit

- (1) VCC PINS CONNECTED TO POWER SUPPLY = 5.0V +/- 10%
 GND PINS CONNECTED TO COMMON GROUND
- (2) A(J0) / A(Q2) / A(U4) / A(O6) CONNECTED TO GND
 A(Q8) / A(T0) / A(L2) / A(L4) CONNECTED TO GND
 A(U7) / A(Q3) / A(U5) / A(U7) CONNECTED TO VCC THRU 2K OHM RESISTOR
 A(J9) / A(I1) / A(L3) / A(L5) CONNECTED TO VCC THRU 2K OHM RESISTOR
- (3) DQA(O0) / DQA(O2) / DQA(O4) / DQA(O6) CONNECTED TO VCC/2 THRU 2K OHM RESISTOR
 DQA(O7) / DQA(O3) / DQA(O5) / DQA(O7) CONNECTED TO VCC/2 THRU 2K OHM RESISTOR
 DQB(O0) / DQB(O2) / DQB(O4) / DQB(O6) CONNECTED TO VCC/2 THRU 2K OHM RESISTOR
 DQB(O1) / DQB(O3) / DQB(O5) / DQB(O7) CONNECTED TO VCC/2 THRU 2K OHM RESISTOR
- (4) EN1_ / EN2_ CONNECTED TO GND
 EN3_ / EN4_ / LE CONNECTED TO VCC THRU 2K OHM RESISTOR
- (5) MDEA_ / MDEB_ / WEA_ / WEB_ CONNECTED TO GND
 DIR1A / DIR1B / DEB_ / DES_ CONNECTED TO VCC THRU 2K OHM RESISTOR
- (6) ALL RESISTOR ARE +/- 5% TO 10% AND 1/4W TO 1/2W
- (7) TA SHALL BE AT ROOM AMBIENT OR 25°C +/- 5°C
- (8) VCC/2 = 2.5V +/- 0.5V

Designed by : JUAN R LANDER 08/08/91

Approved by : ALIX DUVALSAINT 08/08/91